



TeloSystems
Bridging Communication Gap

OLED Screen

Intuitive display readable from multiple angles



PTT Button

Textured surface with positive feedback



Radio Design Interface

Powerful compatibility for radio accessories



3G/4G



Android 5.1



IP67
1.8m Drop Test



Crystal Clear Audio



3600
mAh Battery



NFC
(Optional)

TeloPTT TE390

Simplified LTE Handheld Device

Compact, Durable, Handy

www.telosystems.com

TECHNICAL SPECIFICATION

Connectivity		Specifications
Frequency Band	Global Version: GSM: B2/B3/B5/B8 WCDMA: B1/B2/B5/B8 TD-SCDMA: B34/B39 FDD-LTE: B1/B3/B7/B8/B20/B28A/B28B TDD-LTE: B38/B39/B40/B41 American Version: GSM: B2/B5 WCDMA: B1/B2/B4/B5/B19 FDD-LTE: B1/B2/B4/B5/B7/B12/B17/B19/B28A/B28B	
WIFI	IEEE802.11a/b/g/n(2.4G, 5G)	
Bluetooth	BT v4.0 with BLE/ BT2.1+EDR(Enhanced Data Rate)	
GPS	GPS/GLONASS/AGPS	
Hardware		Specifications
CPU	MediaTek Quad-core	
Memory	RAM+ROM: 1GB + 8GB	
Display	OLED 0.97", 128*64 RGB	
Speaker	2.0W, Ø36mm	
Battery	Li-Po 3600mAh	
USB Port	Micro USB2.0	
Interface	M6 Interface for Remote Speaker Microphone, Earpiece	
Sensor	3D Gravity Sensor, Acceleration Sensor	
Software		Specifications
Operation System	Android 5.1	
Physical		Specifications
Dimensions (H x W x D)	117*60*29.2mm	
Weight	182g	
Protection Rating	IP67, 1.8m Drop Test	
Working Temperature	-20°C ~ 60°C	
Storage Temperature	-30°C ~ 70°C	



Construction



Fire Department



Manufacturing



Logistics



Hospitality

Reliable and Flexible

4/F, Chuangye Building, Seven-Star Park, Yu'an 2nd Road, Bao'an District, Shenzhen, China

www.telosystems.com

Tel: +86 755 86950766

Fax: +86 755 86950708

Email: sales@telosystems.com